rhombus

R200 Mini Dome Camera

Ideal for general visibility in most environments

Starts at **$499**

Overview

No bulky hardware, hard drives, or complex software. The R200 simplifies the entire video security experience with an intelligent, all-in-one camera.

With a quad-core processor and vandal-resistant exterior, the R200 delivers incredible performance and reliability right out of the box. For organizations that require greater insights and visibility across their facilities, the R200 is compatible with the entire line of Rhombus IoT Sensors.

Up to 5MP Full-HD video

2.8mm focal length

116° Diagonal FoV
104° Horizontal FoV
 87° Vertical FoV

5MP image sensor
2592 x 1944 resolution

R200 Camera Specs

IP66 Weather Resistance and IK10 Impact Resistance

Onboard Storage Included*: 128GB (20 days), 256GB (40 days), 512GB (90 days), 1TB (180 days)
*Optional unlimited cloud archiving available

Night Vision: Infrared illuminators (100ft in low light)

Aperture: F/2.0

Pan / Tilt / Zoom: Up to 2X digital PTZ

Ethernet: 10 / 100Mbps, MDI/MDI-X Auto Sensing

Power-over-Ethernet: Standard 802.3af for one-cable installation

Power Consumption: Max 10.5 watts

Dimensions: 118mm (4.64in) x 90mm (3.54in)

Operating Temperature: -20° to 50°C (-4° to 122°F)

Operating Humidity: <95% RH

In the Box: Torx key, mounting screws, anchors, waterproofing kit

Baseline Steady State: 10 - 30 Kbps per camera

HD WAN Live Streaming: 530 - 720 Kbps per camera

CE, FCC, IC, UK, AUS, NZ, NDAA, TAA Compliant

Rhombus Sensor Network Compatible

Rhombus 10-Year Warranty Included